

540326

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)


PCT

(10) International Publication Number
WO 2005/040531 A1

- (51) International Patent Classification⁷: **E05B 73/00**, G08B 13/14
- (21) International Application Number: PCT/GB2004/004364
- (22) International Filing Date: 14 October 2004 (14.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0324341.7 17 October 2003 (17.10.2003) GB
- (71) Applicant (for all designated States except US): **DUBOIS LIMITED** [GB/GB]; Amaray House, Arkwright Road, Corby, Northants NN17 5AE (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MADDOX, Sean, Geoffrey** [GB/GB]; 17A St. Marys Street, Stamford, Lincs PE9 2DG (GB). **FARRAR, Peter, Antony** [GB/GB]; Glenelg, Low Barn, Burley Lane, Menston, Leeds LS29 6EX (GB). **JOHNSTON, Robert** [GB/GB]; Smarker House, 22 Newton Road, Geddington, Northants NN14 1AU (GB).
- (74) Agents: **UNWIN, Stephen, Geoffrey et al.**; Fry Heath & Spence LLP, The Gables, Massetts Road, Horley, Surrey RH6 7DQ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: APPARATUS FOR RELEASING MAGNETIC SECURITY DEVICE



(57) Abstract: Apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article. The apparatus has a first portion (1) for locating an article in a first direction (D1) and a second portion (2) for locating an article in a second direction (D2) perpendicular to the first direction (D1), so providing an L-shaped slot or receptacle capable of receiving articles of a wide range of shapes and sizes having a security device installed adjacent two substantially perpendicular sides thereof. The first and/or second portions include magnetic release means for releasing a lock securing the security device to the article and arranged to assist in locating the article in a third direction (M) perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions to align the magnetic security device with the magnetic release means.

WO 2005/040531 A1

WO 2005/040531 A1



— with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

APPARATUS FOR RELEASING MAGNETIC SECURITY DEVICE

TECHNICAL FIELD

This invention relates to apparatus for releasing a magnetic security device used to inhibit unauthorised access to or unauthorised removal of an article for sale. Although applicable to a wide range of articles, it is particularly suited for releasing a security device within a container housing some form of information storage media, for example a CD or DVD. The invention also relates to a method of releasing a magnetic security device using such apparatus.

BACKGROUND ART

The invention is an extension of apparatus described in GB2371597A, the disclosure of which is incorporated herein. This apparatus is also disclosed in WO 02/39451.

GB2371597A describes the principles of operation of a magnetic security device of the type described therein and of the apparatus used to release the security device. The embodiments described in GB2371597A relate to apparatus specifically designed to release such a security device from a CD or DVD box.

A 'magnetic' security device is to be understood as including devices which comprise one or more magnets and/or comprise components capable of being attracted by a magnet, e.g. a metal arm formed of steel or a non-magnetic arm with a magnet or steel component secured thereto.

The present invention seeks to provide apparatus which provides further advantages over this prior art.

SUMMARY OF INVENTION

According to a first aspect of the invention there is provided apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article, the apparatus comprising: a first portion for locating an article in a first direction (D1) and a second portion for

locating an article in a second direction (D2) substantially perpendicular to the first direction (D1), so the article is physically restrained in only the first and second directions (D1, D2) as it is brought into contact with the first and second portions; the first and/or second portions including magnetic release means arranged to assist in locating the article in a third direction (D3) substantially perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means.

According to a second aspect of the invention there is provided apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article, the apparatus comprising: a first portion for locating an article in a first direction (D1) and a second portion for locating an article in a second direction (D2) substantially perpendicular to the first direction (D1), so as to provide an L-shaped slot or receptacle capable of receiving articles of a wide range of shapes and sizes having a security device installed adjacent two substantially perpendicular sides thereof, the first and/or second portions including magnetic release means.

Preferably, the magnetic release means is arranged to assist in locating the article in a third direction (D3) substantially perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means.

According to another aspect of the invention there is provided a method of releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article comprising the steps of providing apparatus as defined above and presenting an article with a magnetic security device thereto to release the magnetic security device therefrom.

BRIEF DESCRIPTION OF DRAWINGS

The invention will now be further described, merely by way of example, with reference to the accompanying drawings, in which:

Figures 1A, 1B, 1C and 1D show a perspective view, plan view, side view and front view, respectively, of a first embodiment of apparatus according to the invention (with a cover shown in an open position);

Figures 2A, 2B, 2C and 2D correspond to Figures 1A, 1B, 1C and 1D, respectively; but with the cover shown in a closed position;

Figures 3A, 3B, 3C and 3D show a perspective view, plan view, side view and front view of a first component of the apparatus shown in Figure 1;

Figures 4A, 4B, 4C and 4D show a perspective view, plan view, side view and front view of a second component of the apparatus shown in Figure 1;

Figures 5A, 5B and 5C show perspective views of a second embodiment of apparatus according to the invention and a first component and second component thereof, respectively;

Figure 6 is a side view of apparatus such as that shown in Figure 1 illustrating its use release a security device from an article; and

Figure 7 is a perspective view of magnets used in the apparatus shown in the preceding figures.

DESCRIPTION OF PREFERRED EMBODIMENTS

The apparatus shown in Figures 1-4 comprises a base portion 1 and a top portion 2. Figures 1-2 show the apparatus when these two portions are assembled together and Figures 3 and 4 respectively show the first and second portions separately. The base portion 1 incorporates a first part 3 of magnetic release means (shown in dotted lines in Fig 1C) and the top portion 2 incorporates a second part 4 of the magnetic release means. In the embodiment

shown, the first part of the magnetic release means comprises a first magnet 3 which is concealed beneath an upper surface 1A of the base portion 1 (and so is not visible in Figure 1A). The second part of the magnetic release means comprises a second magnet 4 mounted adjacent a front face 2A of the top portion 2. The first and second magnets are arranged to apply magnetic forces to a security device in two substantially perpendicular directions.

The first and second magnets 3 and 4 will be described further below with reference to Figure 7.

The base portion 1 presents a flat upper surface 1A upon which an article with a security device is placed so as to locate the article in a vertical direction D1. The top portion 2 presents a front face 2A incorporating the second magnet 4. In the embodiment shown, part of the second magnet 4 projects slightly (e.g. by 1 or 2 mm) from the front surface 4A and the article is moved into contact with this so as to locate the article in a horizontal, forward/backward direction D2.

The magnets 3 and/or 4 are arranged to assist in locating the article in the horizontal, lateral direction D3 as the article is moved into contact with the base portion 1 and top portion 2 so as to align the magnetic security device thereof with the first and/or second magnets 3 and 4.

The article is thus physically restrained in only the first and second directions D1, D2 as it is brought into contact with the first and second portions 1, 2. It has been found that the magnetic attraction between the magnets 3 and/or 4 and the magnetic security device is sufficient to ensure the article is located in the lateral direction D3 with the magnetic security device in alignment with the first and/or second magnets 3, 4 if the article is presented in approximate alignment therewith. There is therefore no need to provide any lateral guides or restraints to assist in locating the article laterally. There is also no need to provide an upper guide for guiding or restraining an upper surface of the article as it can be located vertically simply by being moved into contact with the base portion 1.

Such an arrangement thus removes any limitation on the height or width of an article that can be presented to the apparatus to release a magnetic security device therefrom. This enables the same apparatus to be used to release security devices installed in a wide variety of products (which may be of many different shapes or sizes). The retail outlet can thus use the same apparatus to release security devices from articles such as CD or DVD boxes and from other articles such as boxes, enclosures, capsules or packaging used to house or display other goods, e.g. high value items and/or potentially dangerous items, to which it is desirable to inhibit unauthorised access. Such goods may, for example, include memory cards (recorded or unrecorded), jewellery, medicaments and pharmaceuticals. A wide variety of other goods can be packaged in a manner which requires release of a security device of the type referred to above to permit access to an/or removal of the goods and which can be released using this apparatus.

The apparatus thus presents an L-shaped slot or receptacle capable of receiving articles of a wide variety of shapes and sizes. This L-shaped slot or receptacle is formed by two substantially perpendicular surfaces without other components restricting the shape or size of the article which can be presented thereto so long as the article has two substantially perpendicular sides for locating against these two surfaces. Articles can also be presented to the apparatus from a variety of angles or directions so long as they are brought into engagement with the said two surfaces. There is therefore no need for the article to be presented along a specific, constrained pathway.

The base portion 1 is preferably designed so that it can be securely fastened to a surface, e.g. of a counter adjacent a sales till. The base portion 1 may be bolted to the surface and Figure 1A shows covers 1B and 1C covering through-holes housing two such bolts.

The apparatus is also preferably arranged so that it can be locked in an inoperative mode to prevent unauthorised use, e.g. when a retail outlet is

closed. The embodiment shown in Figures 1 and 2 is provided with a slidable or pivotable cover 5 (shown in the open position in figure 1 and in the closed position in Figure 2). When closed, edges of the cover 5 fit within a groove 6 around the periphery of the surface 1A and the cover 5 can be secured in this position by means of a lock 7.

As shown in Figures 1B and 1C, a portion 4A of the second magnet 4 preferably projects a small distance out of the plane of the front face 2A of the top portion 2. As explained in GB2371597A, during the release operation, the security device is preferably pressed further into the article to assist in the release of a locking mechanism locking it to the article. The portion 4A of the second magnet should thus be of similar size, or smaller, than a head of the security device so, when an article is positioned so that the portion 4A engages the head of the security device, the article can be pushed towards the face 2A so the portion 4A pushes the security device further into the article.

Figures 2A, 2B, 2C and 2D show views corresponding to those of Figures 1A, 1B, 1C and 1D and show the same apparatus but with the cover 5 in the closed position.

The apparatus is preferably designed so the base and top portion 1 and 2 can be made separately and then assembled together. Figures 3A, 3B, 3C and 3D respectively show a perspective view, plan view, side view and front view of the base portion 1. As shown, the base portion 1 includes a recess 1D into which part of the top portion 2 fits.

Figures 4A, 4B, 4C and 4D respectively show a perspective view, plan view, side view and front view of the top portion with the second magnet 4 installed therein (but excluding the cover 5). The second magnet 4 is mounted in a support 8 which projects from the underside of the top portion 2 and fits within the recess 1D when the top portion 2 is assembled with the base portion 1.

Figure 5A is a perspective view of a second embodiment of apparatus according to the present invention again comprising a base portion 10 and a top portion 11 with magnetic release means therein. Although of slightly different shape, this is similar to the first embodiment except that it is not provided with a lockable cover 5 but instead has a lock 12 positioned in the top portion 11. In the locked configuration shown, an obstructing member 13 is locked in a projecting position which prevents an article being brought into a position in which the magnetic release means is able to release a security device therein.

Figures 5B and 5C are perspective views of the top portion 11 and base portion 10 prior to assembly.

Figure 6 illustrates the use of apparatus of the type described above to release a magnetic security device 20 from an article 21 (shown in dotted lines).

As described above, the apparatus comprises a base portion 22 with a first magnet 23 therein (shown in dotted lines) and a top portion 24 with a second magnet 25 therein (also shown in dotted lines). The magnetic security device 20 comprises a plastics component 26 with a head portion 26A, a long arm 26B and a short arm 26C. A metal insert 27 is provided in the head portion 26A and a metal locking member 28 is movably mounted on the long arm 26B. The security device is installed in the article 21 so that the head portion 26A lies adjacent a first side 21A of the article and the long arm 26B lies adjacent a second side 21B of the article (the first and second sides 21A and 21B being adjacent each other and substantially perpendicular to each other).

The article 21 is presented to the apparatus in the appropriate orientation so that the head portion 26A of the security device therein is positioned approximately in alignment with the second magnet 25. The magnetic attraction between the second magnet 25 and the metal insert 27 in the head portion 26A of the security device assists in bringing the head portion 26A into alignment with the second magnet 25.

When the article 21 is pressed towards the top portion 24, a projecting portion of the second magnet 25 serves to push the security device 20 further into the article 21 to disengage locking arm 28 from a detent (not shown) therein. The first magnet 23 is then able to move the locking member 28 downwards to prevent it re-engaging with the detent. If the article 21 is then pulled away from the apparatus, the security device 20 is held stationary by the magnets 23 and/or 25 so is at least partially withdrawn from the article 21 as the article is moved away from the apparatus.

Thus, the second magnet 25 acts to attract the security device in the direction D2 whilst the first magnet 23 acts to attract the locking arm in the direction D1.

Figure 7 is a perspective view of first and second magnets 30, 31 as used in the apparatus described above.

The first magnet 30 which is mounted in the base portion is made up of four pieces assembled in the form of a T. The four pieces are secured or held in the configuration shown by being fitted within a support member (not shown) and/or by adhesive. The centre magnet 30A is orientated with its magnetic axis vertical and its North Pole uppermost. The three magnets 30B, 30C and 30D assembled around this are orientated with their magnetic axes horizontal and their North Poles innermost, i.e. adjacent the centre magnet 30A.

The second magnet 31 which is mounted in the top portion is made up of five pieces assembled in the form of a cross. The five pieces are held in the configuration shown by a support member 8 (as shown in Figures 1, 4 and 5) and/or are secured together, e.g. by means of adhesive. The centre magnet 31A is orientated with its magnetic axis horizontal and its South Pole at the front end which projects from the front face 2A of the top portion. The four magnets 31B, 31C, 31D and 31E are assembled around the centre magnet 31A with their magnetic axes perpendicular to that of the centre magnet 31A and their South Poles innermost, i.e. adjacent the centre magnet 31A. The polarity of all the parts could also be arranged the other way around.

The configuration of both the first and second magnets 30, 31 is such that the pieces thereof tend to repel each other. They therefore have to be held in the configurations shown by being mounted in appropriate supports within the top portion and base portion and/or by suitable adhesive. It is found that the complex magnetic fields created by this arrangement of magnets provide the required forces which attract the head of the security device towards the second magnet 31 and enable the first magnet 30 to move the locking arm 28 so as to unlock the security device 20 so it can be separated from the article 21. Other configurations of magnets for performing this function are also possible.

As indicated above, the apparatus described herein can be used with a wide variety of articles of different shapes and sizes, in particular articles which are of a size and/or shape which could not be inserted into a narrow rectangular opening as provided in the apparatus described in GB2371597A. The security device of the type described and/or as illustrated in Figure 6 can be used in many different articles so long as the article has a first side into which the arms thereof can be inserted such that the head of the device lies adjacent the first side and a second side adjacent to the first side and adjacent which the locking arm of the device is positioned so it can be moved by a magnetic field applied through said second side.

CLAIMS

1. Apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article, the apparatus comprising: a first portion for locating an article in a first direction (D1) and a second portion for locating an article in a second direction (D2) substantially perpendicular to the first direction (D1), so the article is physically restrained in only the first and second directions (D1, D2) as it is brought into in contact with the first and second portions; the first and/or second portions including magnetic release means arranged to assist in locating the article in a third direction (D3) substantially perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means.
2. Apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article, the apparatus comprising: a first portion for locating an article in a first direction (D1) and a second portion for locating an article in a second direction (D2) substantially perpendicular to the first direction (D1), so as to provide an L-shaped slot or receptacle capable of receiving articles of a wide range of shapes and sizes having a security device installed adjacent two substantially perpendicular sides thereof, the first and/or second portions including magnetic release means.
3. Apparatus as claimed in claim 1 or 2 in which the first portion defines a first plane and the second portion defines a second plane substantially perpendicular to the first plane.
4. Apparatus as claimed in claim 3 in which the first and second planes define a slot having a substantially L-shaped cross-section.

5. Apparatus as claimed in any preceding claim in which the first and second portions respectively comprise a base portion and a top portion upstanding therefrom.
6. Apparatus as claimed in claim 5 in which the first and second portions are connected together by means of at least one mutually engageable projection and recess.
7. Apparatus as claimed in any preceding claim in which the magnetic release means is arranged to provide a first magnetic force in a first direction D1 and a second magnetic force in a second direction D2.
8. Apparatus as claimed in claim 7 in which a first magnet mounted in the first portion provides the magnetic force in direction D1 and a second magnet mounted in the second portion provides the magnetic force in the second direction D2.
9. Apparatus as claimed in claim 8 in which the first and/or second magnet comprises a plurality of parts which are held together in a configuration in which they tend to repel each other.
10. Apparatus as claimed in claim 9 in which the first and/or second magnets comprise a central part with a plurality of further parts adjacent thereto, the magnetic axes of each of the further parts being perpendicular to that of the central part.
11. Apparatus as claimed in any preceding claim having closure means moveable between an open position which provides access to the magnetic release means and a closed position which prevents an article being presented to the magnetic release means.
12. Apparatus as claimed in claim 11 in which the closure means comprises a slidable or pivotable cover.
13. Apparatus as claimed in claim 11 or 12 having locking means for locking the closure means in the closed position.

14. Apparatus as claimed in claim 2 or any claim dependent thereon in which the first and/or second portions are arranged to assist in locating the article in a third direction (D3) substantially perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means.
15. A method of releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article comprising the steps of providing apparatus as claimed in any preceding claim and presenting an article with a magnetic security device thereto to release the magnetic security device therefrom.





AMENDED CLAIMS

**[Received by the International Bureau on 24 March 2005 (24.03.2005):
original claims 1-15 replaced by amended claims 1-14; (3 pages)]**

1. Apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article, the apparatus comprising: a first portion for locating an article in a first direction (D1) and a second portion for locating an article in a second direction (D2) substantially perpendicular to the first direction (D1), the first and second portions forming a slot for receiving the article but physically restraining the article in only the first and second directions (D1, D2) as it is brought into in contact with the first and second portions; the first and/or second portions including magnetic release means arranged to assist in locating the article in a third direction (D3) substantially perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means, the magnetic release means being arranged to provide a first magnetic force in the first direction D1 and a second magnetic force in the second direction D2 for releasing a magnetic security device from the article
2. Apparatus for releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article, the apparatus comprising: a first portion for locating an article in a first direction (D1) and a second portion for locating an article in a second direction (D2) substantially perpendicular to the first direction (D1), so as to provide an L-shaped slot or receptacle capable of receiving articles of a wide range of shapes and sizes having a security device installed adjacent two substantially perpendicular sides thereof, the first and/or second portions including magnetic release means arranged to provide a first magnetic force in the first direction D1 and a second magnetic force in the second direction D2 for releasing a magnetic security device from the article.

3. Apparatus as claimed in claim 1 or 2 in which the first portion defines a first plane and the second portion defines a second plane substantially perpendicular to the first plane.
4. Apparatus as claimed in claim 3 in which the first and second planes define a slot having a substantially L-shaped cross-section.
5. Apparatus as claimed in any preceding claim in which the first and second portions respectively comprise a base portion and a top portion upstanding therefrom.
6. Apparatus as claimed in claim 5 in which the first and second portions are connected together by means of at least one mutually engageable projection and recess.
7. Apparatus as claimed in any preceding claim in which a first magnet mounted in the first portion provides the magnetic force in direction D1 and a second magnet mounted in the second portion provides the magnetic force in the second direction D2.
8. Apparatus as claimed in claim 7 in which the first and/or second magnet comprises a plurality of parts which are held together in a configuration in which they tend to repel each other.
9. Apparatus as claimed in claim 8 in which the first and/or second magnets comprise a central part with a plurality of further parts adjacent thereto, the magnetic axes of each of the further parts being perpendicular to that of the central part.
10. Apparatus as claimed in any preceding claim having closure means moveable between an open position which provides access to the magnetic release means and a closed position which prevents an article being presented to the magnetic release means.
11. Apparatus as claimed in claim 10 in which the closure means comprises a slidable or pivotable cover.

- 12.Apparatus as claimed in claim 10 or 11 having locking means for locking the closure means in the closed position.
- 13.Apparatus as claimed in claim 2 or any claim dependent thereon in which the first and/or second portions are arranged to assist in locating the article in a third direction (D3) substantially perpendicular to the first and second directions (D1, D2) by magnetic attraction of the security device as the article is brought into contact with the first and second portions so as to align the magnetic security device with the magnetic release means.
- 14.A method of releasing a magnetic security device used to inhibit unauthorised access to and/or unauthorised removal of an article comprising the steps of providing apparatus as claimed in any preceding claim and presenting an article with a magnetic security device thereto to release the magnetic security device therefrom.






FIG. 2B.




FIG. 2D




FIG. 2A




FIG. 2C.




FIG. 3B




FIG. 3D




FIG. 3A








FIG. 3C






FIG. 5B




FIG. 5C




FIG. 5A




FIG. 6.




FIG. 7

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/GB2004/004364

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E05B73/00 G08B13/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 E05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US 2002/000111 A1 (BELDEN DENNIS D ET AL) 3 January 2002 (2002-01-03) paragraphs '0061!', '0062!	1-5, 14, 15 7, 8, 11-13
Y	EP 1 298 268 A (WEISSKOPF JOHANN GEORG) 2 April 2003 (2003-04-02) paragraph '0021!	7, 8
Y	WO 01/31152 A (MW TRADING APS ; HOLMGREN BERTIL (SE)) 3 May 2001 (2001-05-03) figures	11-13
A	US 2003/094021 A1 (TAKINAMI MASASHI) 22 May 2003 (2003-05-22) figures	1, 2, 15
	----- -/-- -----	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

18 January 2005

Date of mailing of the international search report

26/01/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Westin, K

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB2004/004364

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01/20107 A (ALPHA SECURITY PRODUCTS) 22 March 2001 (2001-03-22) figures	1,2,15
A	WO 01/83325 A (ALPHA SECURITY PRODUCTS INC) 8 November 2001 (2001-11-08) figures	1,2,15
A	GB 2 371 597 A (DUBOIS LTD) 31 July 2002 (2002-07-31) cited in the application figures	1,2,15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB2004/004364

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2002000111	A1	03-01-2002	AU 7366401 A WO 0202895 A2	14-01-2002 10-01-2002
EP 1298268	A	02-04-2003	EP 1298268 A1	02-04-2003
WO 0131152	A	03-05-2001	SE 515061 C2 AU 1424701 A EP 1224372 A1 PL 354652 A1 WO 0131152 A1 SE 9903960 A TW 460654 B	05-06-2001 08-05-2001 24-07-2002 09-02-2004 03-05-2001 30-04-2001 21-10-2001
US 2003094021	A1	22-05-2003	JP 2003155085 A	27-05-2003
WO 0120107	A	22-03-2001	AU 7582900 A WO 0120107 A2	17-04-2001 22-03-2001
WO 0183325	A	08-11-2001	AU 5747601 A WO 0183325 A2 US 2002003095 A1	12-11-2001 08-11-2001 10-01-2002
GB 2371597	A	31-07-2002	AU 1414602 A BR 0115236 A CA 2427634 A1 CN 1486387 T EP 1336177 A2 WO 0239451 A2 JP 2004513043 T PL 361665 A1 US 2004123311 A1	21-05-2002 17-02-2004 16-05-2002 31-03-2004 20-08-2003 16-05-2002 30-04-2004 04-10-2004 24-06-2004